

30KW Perkins silent diesel generator【1103A-33G】



KEY SPECIFICATIONS

| | |
|--------------------|----------|
| PRIME POWER | 30KW |
| PHASE | 3 |
| DRY WEIGHT | 800kg |
| LENGTH | 2100mm |
| WIDTH | 900mm |
| HEIGHT | 1250mm |
| FUEL TANK CAPACITY | >8 hours |

FEATURES & BENEFITS

- 30KW@ 60Hz Perkins engine
- High quality and reliable 3 cylinder diesel engine
- All copper brush-less generator
- With Fireproof, soundproof, rainproof canopy

- High temperature and low oil, water and fuel protection to protect against engine damage
- Easy to use 6110 digital controller with auto and manual start options
- All sets under go a comprehensive testing / before delivery inspection prior to delivery
- Peace of mind of earlier of one year/1000 hour warranty

GENSET SPECIFICATIONS

ENGINE

Perkins diesel engine:1103A- 33G
 cylinder, water cooled
 Electronic governor control system
 DC starter and charge alternator
 Replaceable fuel filter oil filter and dry element air filter
 Cooling radiator and fan
 Fuel connection hoses and manual sump oil drain valve
 Exhaust silencer
 Maintenance free battery including rack and cables
 Perkins engine manual

ALTERNATOR

Full copper, brushless
 Single bearing system, four poles
 Insulation class H with circuit breaker protection
 Standard degree of protection IP21-23
 Self-exciting and self-regulating
 AVR included
 Screen protected and drip proof
 Stator winding with 2/3 pitch for improved harmonics
 Close voltage regulation

CHASSIS

Steel chassis and anti-vibration pads
 Base frame incorporates integral fuel tank
 The generator can be lifted or pushed/pulled by the base frame
 Includes diesel level sensor information to the controller

CANOPY

Easy maintenance and operation
 Easy lifting and moving
 Insulated engine exhaust system
 Exterior emergency stop push button
 48 hours build in fuel tank

CONTROL SYSTEM

Control supervision and protection panel is mounted on the genset base frame. The control panel is equipped as follows:

AUTO MAINS FAILURE CONTROL PANEL

6110 electronic controller
Emergency stop push button
Static battery charger

GENERATING SET CONTROL MODULE 6110N FEATURES

This module is used to monitor a mains supply and automatically start a standby generating set
Microprocessor based design
Monitors engine performance and AC power output
LCD and LED alarm indication; GSM SMS input slot (as optional extra)
Front panel configuration of timers and alarm trip points
Provides signal to change over switch panel
Event logging and shutdown alarms
Remote communication via RS232 port or RS485 output
Easy push button control
STOP/RESET-MANUAL-AUTO-TEST-START
Operation indicators accessed by the LCD display
Scroll push button

METERING VIA LCD DISPLAY

Generator volts (L-L/L-N); mains volts (L-L/L-N)
Generator amps (L1, L2, L3, N); generator (kVA and kW)
Generator frequency
Engine hours run; plant battery (volts)
Engine oil pressure (psi and bar)
Engine speed (rpm)
GSM SMS signal
Phase rotation
Engine temperature (°C)

AUTOMATIC SHUTDOWN AND FAULT CONDITIONS

Under/over speed; fail to start
High engine temperature; fail to stop
Low oil pressure; charge fail
Under/over generator volts; over current
Under/over generator frequency; emergency stop
Under/over mains frequency
Under/over mains voltage
Low/high battery volts

30KW Silent Diesel generator set technical parameters

| | | |
|----------------------|--------------------------------|-------------------------------|
| Diesel generator set | GENERATOR | LEROY SOMER TAL-A42-E |
| | Model | DGS-PK30S |
| | Power | 30KW |
| | Current | 100.2 A) |
| | Rated frequency | 60 (Hz) |
| | Start-up time | 5~6 (S) |
| | Power factor | 0.8 |
| | Rated voltage | 110/220(V) |
| Perkins Engine | Model | 1103A-33G |
| | Gross Mechanical Output | 35.4KW/47.5KW |
| | Rated speed | 1800 (r/min) |
| | Cycle way | 4-stroke |
| | Cylinders | 4 |
| | Displacement | 3.3L |
| | Compression ratio | 17.3:1 |
| | speed control mode | MECANICO |
| | Starting | DC |
| | Intake system | Naturally aspirated |
| | Exhaust gas temperature | ≤530°C |
| | Maximum exhaust back pressure | 100kPa |
| | 100% Prime Power Load | < 203g/kwh |
| | 50% Prime Power load | < 210g/kwh |
| | Oil capacity | 8.30L |
| | Rated speed hydraulic | 286-484kPa |
| | Cooling | Closed cycle water cooling |
| | Coolant capacity | 10.2L |
| Open temperatures | 380-410°C | |
| Maximum temperature | 95°C | |
| Alternator | Phase | 1 phase 3 wires |
| | Generating capacity | 30KW |
| | Generator efficiency | 95% |
| | Overload | 10% overload can run 1h/2h |
| | Protection class | IP21-23 |
| | Insulation class/ level rise | H/H |
| | Telephone influence factor THF | < 50 |
| | Altitude | ≤1000m |
| GENSET | Voltage setting range | ≥±5% |
| | Transient frequency deviation | ≤ - 10% |
| | Frequency Recovery time | ≤5S |
| Silent type | Dimensions | 2100 (mm) *900(mm)*1250(mm) |
| | Weight | 800(kg) |

Package List (1 Package for 1 set only)

● With, ○ without

| STANDARD ACCESSORIES | Open Type () | Silent Type (●) |
|--|---------------|-----------------|
| Soft pipe for fuel and handle for lube going-out | ● | ● |
| High-efficient silencer (*2) | ● | ● |
| Cooling water tank | ● | ● |
| Exhaust elbow | ● | ● |
| Storage battery system | ● | ● |
| Steel base-frame against vibration | ● | ● |
| Sound-proof & Weather-proof Canopy (super silent type) | ○ | ● |
| Single-bearing generator again drops | ● | ● |
| Intelligent LED display control panel | ● | ● |
| Operation& Maintenance manual. | ● | ● |
| Speed governor | | |
| Electric start and 12V charger system | ● | ● |
| Standard air filter, oil filter, fuel filter | ● | ● |
| ATS | ○ | ○ |
| Base frame fuel tank | ○ | >8H |

